



Main

Range of product	Moduline
Range	Moduline
Product or component type	1 socket-outlet
Device application	Power supply
Colour tint	Silver
Product brand	Schneider Electric
Outlet standard description	Standard earth
Quantity per set	1
Cover type	Hinged lid With shutter
Socket additional information	Lid and shuttered
Market segment	Residential Commercial Hotel

Complementary

Connections - terminals	Screw terminals
Marking location	Marking on surface
Device mounting	Flush Floor mounted Surface
Mounting support	Flush mounting
Fixing mode	By screw
Material	Aluminium alloy
Surface finish	Painted
[In] rated current	13 A
[Ue] rated operational voltage	250 V AC
Network frequency	50/60 Hz
Depth	41 mm
Width	90 mm
Height	90 mm
Fixing center	60.3 mm
Number of poles	2
Poles description	2P + E
Pin number	3
Targeted country	Malaysia Hong Kong, China Singapore

Environment

Standards	BS 1363:2016 MS 589 SS 145
Ambient air temperature for operation	0...45 °C
IP degree of protection	IP23

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	330.0 g
Package 1 Height	5.3 cm
Package 1 Width	9.7 cm
Package 1 Length	9.2 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Weight	7.1 kg
Package 2 Height	14.0 cm
Package 2 Width	29.8 cm
Package 2 Length	39.9 cm
Unit Type of Package 3	P12
Number of Units in Package 3	720
Package 3 Weight	265.6 kg
Package 3 Height	105.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm

Contractual warranty

Warranty	2
----------	---