

A-MAX

Product Catalogue

ELECTRICAL & HARDWARE SUPPLIER MALAYSIA

Version : December 2023



Table of Contents

A-MAX PRODUCTS CATEGORY	
GI Bar Saddle	2
GI Half Saddle	3
Trunking Bracket	4-5
Copper Earth Link	6-7
Flexible Adaptor	8
Clip	9-11
Conduit Clip	12-16
Lid Cover	17
Screw & Nut.....	18
Fan Hook.....	19
Conduit Accessories	20-22
Socket	23
Papaya Bracket	24-26



GI BAR SADDLE



A-MAX 19mm GI Bar Saddle



A-MAX 20mm GI Bar Saddle



A-MAX 25mm GI Bar Saddle

A-MAX GI Bar Saddle

Brand : A-MAX
Material : EG Sheet
Country : Made in Malaysia
Description :

- Heavy gauge material saddle to secure conduit length to surface.
- Installation during the process of construction, electrical equipment, electrical component etc.
- Easy to equip, long life & for use.
- Protection against impact at all temperatures.



GI HALF SADDLE



A-MAX 19mm GI Half Saddle (Premium)
(Thickness : 1.2mm)

A-MAX GI Half Saddle (Premium)

Brand : A-MAX

Material : GI Sheet

Thickness : 1.2mm

Country : Made in Malaysia

Description :

- Heavy gauge material saddle to secure conduit length to surface.
- Installation during the process of construction, electrical equipment, electrical component etc.
- Easy to equip, long life & for use.
- Protection against impact at all temperatures.



TRUNKING BRACKET



A-MAX 2x2 Trunking Bracket
50mm(L) x 25mm(W) x 100mm(H)
2.8mm(thickness) x 25mm(W) flat bar



A-MAX 2x3 Trunking Bracket
75mm(L) x 25mm(W) x 100mm(H)
2.8mm(thickness) x 25mm(W) flat bar



A-MAX 2x4 Trunking Bracket
100mm(L) x 32mm(W) x 112.5mm(H)
2.8mm(thickness) x 32mm(W) flat bar



A-MAX 4x4 Trunking Bracket
100mm(L) x 32mm(W) x 150mm(H)
4.5mm(thickness) x 32mm(W) flat bar



A-MAX 3x6 Trunking Bracket (Eco)
150mm(L) x 25mm(W) x 125mm(H)
4.5mm(thickness) x 25mm(W) flat bar



A-MAX 3x6 Trunking Bracket (Premium)
150mm(L) x 32mm(W) x 125mm(H)
4.5mm(thickness) x 32mm(W) flat bar





A-MAX 4x6 Trunking Bracket

155mm(L) x 32mm(W) x 155mm(H)
4.5mm(thickness) x 32mm(W) flat bar



**A-MAX 140mm x 285mm L Bracket
(Heavy Duty)**

285mm(L) x 140mm(W) x 24mm(H)

A-MAX Trunking Bracket

Brand : A-MAX
Material : Flat bar
Finishing : Zinc plated
Country : Made in Malaysia
Description :

- For the purpose of holding metal trunking.



COPPER EARTH LINK



A-MAX Copper Earth Link
19mm x 1mm x 75mm



A-MAX Copper Earth Link
19mm x 1.6mm ± 0.1 mm x 75mm



A-MAX Copper Earth Link
20mm x 0.8mm ± 0.1 mm x 75mm



A-MAX Copper Earth Link
25mm x 0.8mm x 75mm



A-MAX Copper Earth Link
25mm x 1.6mm x 75mm



A-MAX Copper Earth Link
25mm x 3mm x 75mm





Sample of packing

Size	Standard Packing (pcs)
19mm x 1mm x 75mm	100pcs / pkt
19mm x 1.6mm \pm 0.1mm x 75mm	100pcs / pkt
20mm x 0.8mm \pm 0.1mm x 75mm	100pcs / pkt
25mm x 0.8mm x 75mm	100pcs / pkt
25mm x 1.6mm x 75mm	100pcs / pkt
25mm x 3mm x 75mm	50pcs / pkt

A-MAX Copper Earth Link

Brand : A-MAX
 Material : 100% Pure Copper
 Country : Made in Malaysia
 Propertise : High Power Electric Transmission

Description :

- Copper Earth Link is important when connecting the metal steel/stainless steel/hot dipped galvanised trunking/tray/ladder during installation.
- Copper Earth Link provide connectivity of body earth along the whole installation wiring system and it is for connecting to ground earth by installer.
- Copper Earth Link is very essential to protect any incident from electricity leakage that may danger to humans.



FLEXIBLE ADAPTOR



A-MAX 19mm GI Flexible Adaptor
c/w Lock Nut



A-MAX 25mm GI Flexible Adaptor
c/w Lock Nut



A-MAX 20mm GI Flexible Adaptor
c/w Lock Nut

A-MAX GI Flexible Adaptor

Brand : A-MAX
Material : Aluminium
Country : Made in Malaysia
Description :

- For electrical flexible conduit use.



CLIP



A-MAX K12 Clip



A-MAX K16 Clip



A-MAX K20 Clip

A-MAX K Clip

Brand : A-MAX

Material : Spring steel

Description :

- Support conduit to rod, wire or flange.
- No installation tools required.





A-MAX 1/4 L Channel Clip 二分
2.8mm (thickness) x 25mm (W)
nut size : 1/4



A-MAX 5/16 L Channel Clip 二分半
2.8mm (thickness) x 25mm (W)
nut size : 5/16



A-MAX 3/8 L Channel Clip 三分
2.8mm (thickness) x 25mm (W)
nut size : 3/8



A-MAX 1/2 L Channel Clip (Eco) 半寸
2.3mm (thickness) x 25mm (W)
nut size : 1/2



A-MAX 1/2 L Channel Clip (Premium) 半寸
2.8mm (thickness) x 32mm (W)
nut size : 1/2





A-MAX G Clip
2.8mm (thickness) x 25mm (W)



A-MAX J Hook (Ceiling Clip)
1mm (thickness) x 23mm (W)

A-MAX Clip

- Brand : A-MAX
Material : Flat bar with nut (L Channel Clip) , GI (J Hook)
Finishing : Zinc plated (L Channel Clip & G Clip)
Country : Made in Malaysia
Description :
- Support conduit to rod.
 - No installation tools required.



CONDUIT CLIP



A-MAX 3/4" Conduit Clip
1.5mm (thickness) x 19mm (W)



A-MAX 1" Conduit Clip
1.5mm (thickness) x 19mm (W)



A-MAX 3/4" Wing Screw Conduit Clip
1.5mm (thickness) x 21mm (W)



A-MAX 1" Wing Screw Conduit Clip
1.5mm (thickness) x 21mm (W)

A-MAX Conduit Clip

Brand : A-MAX
Material : GI
Country : Made in Malaysia
Description :

- Support conduit to rod.
- No installation tools required.





A-MAX Tiger Beam Clamp 9-22M



A-MAX 19mm & 25mm Conduit Clip
(Tiger Beam Clamp)



Sample - Tiger Beam Clamp + Conduit Clip

A-MAX Tiger Beam Clamp 9-22M

Material : Mild steel

Finishing : Zinc plated

Description :

- Use to hang conduit or cable from wall and ceiling.
- Supplies with cup point bolts screw, easy installation to beam flange.

A-MAX 19mm & 25mm Conduit Clip (Tiger Beam Clamp)


Material : Mild steel

Finishing : Zinc plated

Description :

- This is used to associate with the main Tiger Beam Clamp.
- Suitable for 19mm & 25mm conduit.





A-MAX 3/8 Beam Clamp (Heavy Duty)



A-MAX 1/2 Beam Clamp (Heavy Duty)

A-MAX Beam Clamp (Heavy Duty)

Material : Mild steel
Finishing : Zinc plated
Description :

- Beam clamp is universal type to secure clamp the beam for hanging stud rod, devices and etc without actual tapping screw to the beam that may deviate the strength of the beam.





**A-MAX U Bracket
(Heavy Duty Beam Clamp)**
2.7mm(L) x 3mm(W) x 6.3mm(H)
3mm (thickness)




**Sample
Beam Clamp (Heavy Duty) + U Bracket**

A-MAX U Bracket (Heavy Duty Beam Clamp)


Description :

- This is used to associate with the main Beam Clamp (Heavy Duty).






19mm Beam Clamp (Cast Iron)
Weight : 140g



35mm Beam Clamp (Cast Iron)
Weight : 270g



45mm Beam Clamp (Cast Iron)
Weight : 320g

Beam Clamp (Cast Iron)

Material : Malleable Cast Iron

Finishing : Zinc plated

Description :

- Beam clamp is universal type to secure clamp the beam for hanging stud rod, devices and etc without actual tapping screw to the beam that may deviate the strength of the beam.



LID COVER



A-MAX GI Lid Cover

A-MAX GI Lid Cover

- Brand : A-MAX
Material : GI sheet or EG sheet
Country : Made in Malaysia
Description :
- For 19mm to 25mm conduit accessories use.



SCREW & NUT



A-MAX 5/32 x 6mm Lid Cover Srew



A-MAX 5/32 x 10mm Dome Cover Screw



A-MAX M6 Spring Nut



A-MAX M8 Spring Nut



A-MAX M10 Spring Nut



A-MAX M12 Spring Nut

A-MAX Spring Nut

Brand : A-MAX
 Finishing : Zinc plated
 Size : Dia 6mm, 8mm, 10mm & 12mm



FAN HOOK



A-MAX 122 Fan Hook

A-MAX 122 Fan Hook

Brand : A-MAX
Material : GI
Finishing : Zinc plated
Country : Made in Malaysia



CONDUIT ACCESSORIES



A-MAX GI 1 Way Box



A-MAX GI 2 Way Box



A-MAX GI 3 Way Box



A-MAX GI 4 Way Box



A-MAX GI Angle Box





A-MAX GI Dome Cover



A-MAX GI Elbow



A-MAX GI Long Bend



A-MAX GI Inspection Tee



A-MAX GI Reducer



A-MAX GI Flexible Adaptor





A-MAX GI Lock Nut



A-MAX GI Lid Cover

A-MAX Conduit Accessories

Brand : A-MAX
Material : Aluminium
Finishing : Matte colour
Country : Made in Malaysia
Size :

- 19mm
- 20mm (JKR Spec)
- 25mm (JKR Spec)



SOCKET



A-MAX 19mm GI Socket (NT)



A-MAX 25mm GI Socket (NT)



A-MAX 20mm GI Socket (NT)



PAPAYA BRACKET



A-MAX 3/4" Papaya Bracket
3/4"(OD) x 1.2mm(thickness) x 18mm(W)



A-MAX 1" Papaya Bracket
1"(OD) x 1.2mm(thickness) x 18mm(W)



A-MAX 1 1/4" Papaya Bracket
1 1/4"(OD) x 1.2mm(thickness) x 18mm(W)



A-MAX 1 1/2" Papaya Bracket
1 1/2"(OD) x 1.2mm(thickness) x 18mm(W)





A-MAX 2" Papaya Bracket
2"(OD) x 1.2mm(thickness) x 18mm(W)



A-MAX 2 ½" Papaya Bracket
2 ½"(OD) x 1.5mm(thickness) x 20mm(W)



A-MAX 3" Papaya Bracket
3"(OD) x 1.5mm(thickness) x 20mm(W)



A-MAX 4" Papaya Bracket
4"(OD) x 2.0mm(thickness) x 21mm(W)





A-MAX 5" Papaya Bracket
5"(OD) x 2.0mm(thickness) x 21mm(W)



A-MAX 6" Papaya Bracket
6"(OD) x 2.4mm(thickness) x 24mm(W)



A-MAX 8" Papaya Bracket
8"(OD) x 2.4mm(thickness) x 24mm(W)

A-MAX Papaya Bracket

Brand : A-MAX
Material : GI
Country : Made in Malaysia

