

HAND CRIMPING TOOL

RATCH TYPE
PVC HANDLE
SMART OPEN-KNOB

KH-2 & KH-5 & KH-6 Non-Insulated Terminal



Model No.	Crimping Range		Weight (kg)	Length (mm)
	mm ²	AWG		
KH-2	0.5-2.5	20-14	0.23	195
KH-5	1.25-5.5	16-10	0.24	195
KH-6	0.75-6	18-10	0.23	195

KH-8 Non-Insulated Terminal



Model No.	Crimping Range			Weight (kg)	Length (mm)
	JIS mm ²	DIN mm ²	AWG		
KH-8	1.25-8	1.5-10	16-8	0.6	250

KH-9 Non-Insulated Terminal



Model No.	Crimping Range			Weight (kg)	Length (mm)
	JIS mm ²	DIN mm ²	AWG		
KH-9	1.25-8	1.5-10	16-8	0.6	250

KH-16 Non-Insulated Terminal



Model No.	Crimping Range			Weight (kg)	Length (mm)
	JIS mm ²	DIN mm ²	AWG		
KH-16	1.25-14	1.5-16	16-5	0.6	280

KH-22 & KH-38 Non-Insulated Terminal



Model No.	Crimping Range			Weight (kg)	Length (mm)
	JIS mm ²	DIN mm ²	AWG		
KH-22	5.5-22	6-25	10-4	0.92	365
KH-38	5.5-38	6-35	10-2	0.92	365

KH-11 Insulated Terminal & Connector



Model No.	Crimping Range			Weight (kg)	Length (mm)
	JIS mm ²	DIN mm ²	AWG		
KH-11	0.25-2	0.25-2	22-14	0.8	270

KH-12 Insulated Terminal & Connector



Model No.	Crimping Range			Weight (kg)	Length (mm)
	JIS mm ²	DIN mm ²	AWG		
KH-12	2-5.5	2-6	16-10	0.8	270

KH-18C Insulated Terminal & Connector



Model No.	Crimping Range		Weight (kg)	Length (mm)
	mm ²	AWG		
KH-18C	10-16	8-6	0.6	270

KH-13 Close-End Terminal



Model No.	Crimping Range			Weight (kg)	Length (mm)
	JIS mm ²	DIN mm ²	AWG		
KH-13	0.5-5.5	0.5-6	20-10	0.6	270

KH-28C Close-End Terminal



Model No.	Crimping Range		Weight (kg)	Length (mm)
	mm ²	AWG		
KH-28C	6-10	10-8	0.6	270

HAND CRIMPING TOOL

Turn left of smart open-knob if the Handles can not be opened due to wrong use.