







ARTFUL LINES OF NATURE

Rinnai



Nature-inspired artistry. Advanced shower technology.

Imagine the ocean waves gently lapping on the shore, curling and washing over the sand and pebbles, leaving traces of parallel lines along the sandy canvas. It is always a mesmerising sight and a source of inspiration and relaxation.

Matte, smooth lines

Aptly named Sen, which means 'line' in Japanese, Rinnai Sen series is inspired by the beautiful lines on sandy beaches. The sleek, parallel lines are aesthetically pleasing and calming to behold, making shower a great retreat from the bustling world for the mind and body.



Simple temperature control

Rinnai Sen series not only exudes the beauty of minimalist design, it also offers ease of control. With a turn of the knob, you can regulate the water temperature from relaxing lukewarm to invigorating hot in seconds.

Silent operation

DC Inverter Pump delivers powerful water pressure yet remarkably silent, enabling you to immerse in a soothing, quiet bath at the same time.

DC Inverter Pump

· Silent operation

• Save up to 50% energy compared to AC Pump

Cost effective and eco-friendly

· Advanced brushless DC motor technology

· Maintenance-free, no carbon brush

Pump speed control, suitable for high and
low water pressure

Longer lifespan

· 5-year warranty



RIDUEL

High-power hot shower



With 3.8kW heating capacity that shortens heating time, Rinnai Sen Series provides hot water faster to give you instantly relaxing hot shower, especially on a cold day.

State-of-the-art features

Rinnai Sen series is designed with simplicity in aesthetics but built with a host of trusted Japanese technologies, ensuring top-notch durability and safety.



1-Knob Control Easy temperature control with a turn.



Earth Leakage Circuit Breaker (ELCB) Cuts off electricity supply in the event of current leakage.



Lightning & Surge Protection Built-in surge protector protects from lightning strikes and current leakage.



Dual Over Temperature Safety Cut-Off Avoids overheating and scalding with auto-reset if water temperature exceeds set limit. (Primary cut-off: 55°C; Secondary cut-off: 90°C)



IP25 Splash-Proof Protection ABS plastic waterproof casing is in compliant with IP25 Safety Standard to prevent water and dust.



Auto Flow Sensor Switch Shuts off heater automatically to avoid dry burn when water flow is too low.

Extra Large (8 inches) Rainshower Head Rainshower set sold seperately.

Splendid Splash

Living up to Japanese culture of incredible attention to detail, Rinnai Sen series comes with meticulously designed shower heads to let you shower just the way you like.

3-Multi Spray Handshower Comes with a choice of 3 classic spray nozzles

Aqua Turquoise (TQ), Sky Blue (BL), Sandy Beach (BG)









Anti-Twist Hose Prevents low water flow due to twisted hose

RRS-C1XX *Without Hand Shower + 1.5m Hose

5-Multi Spray Handshower Comes with a choice of 5 classic spray nozzles

Cirrus Cloud (WH)







Soothing colours

Available in 4 exquisite colours to blend seamlessly with your bathroom tiles.



REI-E380DP-C-BL | REI-E380NP-C-BL



REI-E380DP-B-WH | REI-E380NP-B-WH



REI-E380DP-C-TQ | REI-E380NP-C-TQ



REI-E380DP-C-BG | REI-E380NP-C-BG







Chrome Showerset Model No.	REI-E380DP-C-BG	REI-E380NP-C-BG
	REI-E380DP-C-BL	REI-E380NP-C-BL
	REI-E380DP-C-TQ	REI-E380NP-C-TQ
RCP	RM 656	RM 422
Shower Bracket Model No.	REI-E380DP-B-WH	REI-E380NP-B-WH
RCP	RM 612	RM 352
Rainshower Accessory Model No.	RRS-C1XX	
*Without Hand Shower + 1.5m Hose		
RCP	RM 279	
Specification		
Pump	DC Inverter Pump	Without Pump
Thermostat	Double Action	
Power Rating	3.8kW	
Voltage	240V	
Water Temperature Control	Electronic Control	
Min Flow Rate	2L / min	
Min. Inlet Water Pressure	20 kPa	
Max. Inlet Water Pressure	600 kPa	
Cold Water Connection	15mm diameter Male Thread (1/2'' BSP)	
Water Heater Dimension (W x D x H)	222 x 388 x 102 (mm)	
Water Heater Gift Box (W x D x H)	250 x 590 x 105 (mm)	
Gross Weight (Chrome Showerset)	2.85kg	2.50kg
Net Weight (Chrome Showerset)	1.80kg	1.45kg
Gross Weight (Shower Bracket)	2.55kg	2.20kg
Net Weight (Shower Bracket)	1.80kg	1.45kg
Features		
Earth Leakage Circuit Breaker (ELCB)	√	\checkmark
Lightning & Surge Protection	<u>√</u>	<u></u>
Dual Over Temperature Safety Cut-off	√	√
IP25 Splash-Proof Protection	√	√
Auto Flow Sensor Switch	\checkmark	√.



 $\sqrt{}$

 $\sqrt{}$

 $\sqrt{}$

Х

 \checkmark

 $\sqrt{}$

Rinnai (Malaysia) Sdn Bhd (015790-A)

Electronic Pump Speed Control

High Quality Stop Valve

Anti Leak Heater Tank

D2-3, Block D2, Pusat Dagangan Dana 1, Jalan PJU 1A/46, 47301 Petaling Jaya, Selangor Darul Ehsan, Malaysia. Toll Free 1800-88-8180 Email enquiries@rinnai.com.my Web www.rinnai.com.my