

Scotch® Vinyl Electrical Tape 33

Scotch® Vinyl Electrical Tape 33 is a quality, general-purpose vinyl insulating tape. It has excellent resistance to: abrasion, moisture, alkalies, acid, copper corrosion and varying weather conditions. It is a polyvinyl chloride (PVC) tape that has a high dielectric strength, is flame-retardant and conformable, and provides excellent mechanical protection with minimum bulk. It is a UL Listed "Insulating Tape".

Adhesive Material Rubber Resin

Backing Material Polyvinyl Chloride

Tape Grade Premium

Tape Type Vinyl

Operating Temperature 32–176°F (0–80°C)

RoHS 2011/65/EU Yes

Specifications ASTM D1000

Agency Approvals



Country of Origin



Order No.	UPC	Color	Length	Width	Thickness	Dielectric Strength	Rolls per Carton	Rolls per Case
33-3/4x36YD	054007-10133	Black	36 yd	0.75"	7 mil	1000 mV	12	48
33-1-1/2X44FT	054007-10174	Black	44'	1.50"	7 mil	1000 mV	10	100

Scotch® Vinyl Color Coding Electrical Tape 35

Scotch® Vinyl Electrical Tape 35 is a 7-mil (0.178 mm) thick polyvinyl chloride (PVC) color-coding tape. Outstanding electrical and mechanical properties make this tape excellent for use in phase identification, color coding of motor leads and piping systems, and for marking safety areas. Scotch Tape 35 operates over a wide range of temperatures – between 32–220°F (0–105°C). This tape is available in nine fade-resistant colors.

Adhesive Material	Rubber Resin
Backing Material	Polyvinyl Chloride
Tape Grade	Premium
Tape Type	Vinyl
Operating Temperature	32–220°F (0–105°C)
RoHS 2011/65/EU	Yes
Specifications	VDE 0340- TEIL1

Agency Approvals



Country of Origin



Order No.	UPC	Color	Length	Width	Thickness	Breaking Strength	Rolls per Carton	Rolls per Case
35-BLUE-1/2	054007-10240	Blue	20'	0.50"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-BLUE-3/4	054007-10836	Blue	66'	0.75"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-BROWN-1/2	054007-10299	Brown	20'	0.50"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-BROWN-3/4	054007-10885	Brown	66'	0.75"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-GRAY-1/2	054007-10281	Gray	20'	0.50"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-GRAY-3/4	054007-00072	Gray	66'	0.75"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-GREEN-1/2	054007-10265	Green	20'	0.50"	7 mil	17 lb/in (3.04 kN/m)	10	100

Scotch® Super 33+™ Vinyl Electrical Tape

Scotch® Super 33+™ Vinyl Electrical Tape is a premium grade, 7 mil thick, all-weather vinyl-insulating tape. It is designed to perform continuously between a temperature range of 0–220°F (-18–105°C). It has an excellent resistance to abrasion, moisture, alkalies, acids, corrosion and varying weather conditions (including ultraviolet exposure). The combination of elastic backing and aggressive adhesive provides moisture-tight electrical and mechanical protection with minimum bulk. Scotch Super 33+ Vinyl Electrical Tape is an Underwriters' Laboratories Listed and Canadian Standards Association Certified "Insulating Tape."

Adhesive Material	Rubber Resin
Backing Material	Polyvinyl Chloride
Tape Grade	Premium
Tape Type	Vinyl
Operating Temperature	0–220°F (-18–105°C)
RoHS 2011/65/EU	Yes
Specifications	ASTM D 3005 type 1
Agency Approvals	 
Country of Origin	



Order No.	UPC	Color	Length	Width	Thickness	Dielectric Strength	Rolls per Carton	Rolls per Case
33+SUPER-3/4X36YD	054007-00053	Black	36 yd	0.75"	7 mil	1150 mV	12	48
33+SUPER-3/4X20FT	054007-06130	Black	20'	0.75"	7 mil	1150 mV	10	100
33+SUPER-3/4X66FT	054007-06132	Black	66'	0.75"	7 mil	1150 mV	1	20
33+SUPER-3/4X52FT	054007-06133	Black	52'	0.75"	7 mil	1150 mV	10	100
33+SUPER-3/4X44FT	054007-10075	Black	44'	0.75"	7 mil	1150 mV	10	100
33+SUPER-DISP	054007-10216	Black	66'	0.75"	7 mil	1150 mV	10	100
33+SUPER-1X36YD	054007-08949	Black	36 yd	1.00"	7 mil	1150 mV	12	48
33+SUPER-1-1/2X36YD	054007-50236	Black	36 yd	1.50"	7 mil	1150 mV	-	50

Vinyl Electrical Tapes

Scotch® Vinyl Color Coding Electrical Tape 35 (continued)

Order No.	UPC	Color	Length	Width	Thickness	Breaking Strength	Rolls per Carton	Rolls per Case
35-GREEN-3/4	054007-10851	Green	66'	0.75"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-ORANGE-1/2	054007-10273	Orange	20'	0.50"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-ORANGE-3/4	054007-10869	Orange	66'	0.75"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-RED-1/2	054007-10224	Red	20'	0.50"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-RED-3/4	054007-10810	Red	66'	0.75"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-VIOLET-1/2	054007-49923	Violet	20'	0.50"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-VIOLET-3/4	054007-11271	Violet	66'	0.75"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-WHITE-1/2	054007-10232	White	20'	0.50"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-WHITE-3/4	054007-10828	White	66'	0.75"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-YELLOW-1/2	054007-10257	Yellow	20'	0.50"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-YELLOW-3/4	054007-10844	Yellow	66'	0.75"	7 mil	17 lb/in (3.04 kN/m)	10	100
35-MULTI-COLOR	051131-59073	Multi-pack	20'	0.50"	7 mil	17 lb/in (3.04 kN/m)	4	48