

Product Datasheet: BEL602

Overview

| Product Brand | Belden DataConnect |
|---------------|----------------------|
| Product Name | BEL602 |
| Product Group | CAT 6 UTP LSZH Cable |
| Product Color | White |







Belden DataConnect system is designed to provide standards-compliant cabling solutions for typical Ethernet data applications, include Retail shops, shopping malls & outlets, restaurants, bars/pubs, residential buildings etc., which is suitable for permanent & channel link installation

Construction Specifications

| Conductor Material | Bare Copper | |
|---------------------------|----------------|--|
| Conductor Strands | Solid | |
| Conductor Gauge | 24 AWG | |
| Insulation Material | Polyethylene | |
| Number of Pairs | 4 | |
| Cabling Filler | Central Spline | |
| Overall Diameter (Nom.) | 5.7 mm | |
| Put-up Length | 305M | |
| Bulk Weight | 39 KG/KM | |

Physical Features

| Operating Voltage | 72V DC (max.) | |
|---------------------------|---|---|
| Temperature for Operating | - 20°C to + 60°C | |
| Flame Rating | IEC 60332-1, GB/T 18380.12, AS/NZS1660.5.6 | |
| Reference Standards | IEC 11801 Class E, TIA/EIA 568.2-D Category 6 | _ |

Environmental

| RoHS | Jan, 2013 |
|------|-----------|

Order Information

| Stock Code | Description | Put Up | Ship Weight (kg) | Jacket Color | Package |
|-----------------|--------------------------|--------|------------------|-----------------|---------|
| BEL602 009U305M | Cat 6 UTP 4PR24AWG, LSZH | 305M | 11 | White | Box |

Revision Number: 1 Revision Date: Jul-21-2021