

KH-120 Cable Lug & Aluminum & Copper

With Non-Ratchet Adjusting Screw

Cable Lug: 10-95mm²

Aluminum: AWG8-4/0

Copper: AWG8-250MCM



Model No.	Crimping Range			Weight (kg)	Length (mm)
	DIN (mm ²)	AWG	JIS (mm ²)		
KH-120	10-95	8-4/0	8-80	2.8	558

KH-150 Cable Lug & Aluminum & Copper

With Non-Ratchet Adjusting Screw

Cable Lug: 10-120mm²

Aluminum: AWG8-4/0

Copper: AWG8-250MCM



Model No.	Crimping Range			Weight (kg)	Length (mm)
	DIN (mm ²)	AWG	JIS (mm ²)		
KH-150	10-120	8-250	8-100	3.5	595

KH-170 Cable Lug & Aluminum & Copper

With Non-Ratchet Adjusting Screw



Application	Crimping Range		Weight (kg)	Length (mm)
	mm ²	AWG		
Cable Lug	10-150		3.8	660
Aluminum		8-250MCM		
Copper		8-300MCM		

KH-230 Cable Lug & Aluminum & Copper

With Non-Ratchet Adjusting Screw & Telescopic Lever



Application	Crimping Range		Weight (kg)	Length (mm)
	mm ²	AWG		
Cable Lug	10-240		4.8	978
Aluminum		8-400MCM		
Copper		8-500MCM		

HX-160 & HX-240 & HX-400

Non-Insulated Terminal

With Movable Revolving Dies & Telescopic Lever



Model No.	Crimping Range		Weight (kg)	Length (mm)
	mm ²	AWG		
HX-160	70-150	2/0-300	4.8	978
HX-240	120-240	250-500	4.8	978
HX-400	185-400	300-750	4.8	978

CT-38 Non-Insulated Terminal

With Movable Revolving Dies



Model No.	Crimping Range			Weight (kg)	Length (mm)
	DIN (mm ²)	AWG	JIS (mm ²)		
CT-38	10 / 16 / 25 / 35	8-2	8 / 14 / 22 / 38	2.9	556

CT-60 Non-Insulated Terminal

With Movable Revolving Dies



Model No.	Crimping Range			Weight (kg)	Length (mm)
	DIN (mm ²)	AWG	JIS (mm ²)		
CT-60	16 / 25 / 35 / 50-70	6-2/0	14 / 22 / 38 / 60	3.8	676

CT-80 Non-Insulated Terminal

With Movable Revolving Dies



Model No.	Crimping Range			Weight (kg)	Length (mm)
	DIN (mm ²)	AWG	JIS (mm ²)		
CT-80	10 / 16 / 25 / 35 / 50-70 / 95	8-3/0	8 / 14 / 22 / 38 / 60 / 80	3.9	638

CT-100 & CT-150 Non-Insulated Terminal

With Movable Revolving Dies



Model No.	Crimping Range			Weight (kg)	Length (mm)
	DIN (mm ²)	AWG	JIS (mm ²)		
CT-100	25 / 35 / 50-70 / 95 / 120	4-4/0	22 / 38 / 60 / 80 / 100	4.9	676
CT-150	16-150	4-300MCM	14-150	4.9	710