Product sheet



LEGRAND

Bulkhead light - IP44 - IK06 - oval 60 W- E27 - metal grid no tool - grey

REF. 060414 | EAN. 3245060604141

This bulkhead light is a robust IP44, IK06 oval luminaire with 60W E27 versatility. Its structured glass diffuser and wide beam ensure uniform white light. A durable grey plastic housing with metal grid simplifies installation.

> Visit e-catalogue

Description

This bulkhead light is a robust IP44, IK06 oval luminaire with 60W E27 versatility. Its structured glass diffuser and wide beam ensure uniform white light. A durable grey plastic housing with metal grid simplifies installation.

Product charateristics

- IP 44/54/55 weatherproof bulkhead lights - For domestic, commercial areas and tough environments
- Oval - IP 44 / IK 06 - Polypropylene base - Glass diffuser - Galvanised steel or plastic - Protection wire grid - 3 side knockable entries, for 16, 20 mm - cable - 230 V - 50 Hz - Self - extinguishing : 850 °C - For compact fluorescent lamps - Porcelain lampholder - Screw terminals 12 W - E 27 - Grey - Metal grid - no tool required

Technical characteristics

Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Suitable for workplace according to EN 12464-1	No
Lamp type	Incandescent lamp
With light source	No
Suitable for number of light sources	1
Lamp holder	E27
Housing material	Plastic
Housing colour	Grey

Dimming Zigbee	No
Dimming with push-button	No
Light distributor	Diffuser lens/optic/panel
Light distribution	Asymmetric
Beam angle	> 80° - Extreme wide beam
Light outlet	Direct
Degree of protection (IP), rear side	IP44
degree of impact strength (IK)	IK06
Protection class according to IEC 61140	II
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24	No
Rated ambient temperature according to IEC 62722-2-1 (Min-Max)	-10-40 °C

Material cover	Structured glass
Type of grid	None
Voltage type	AC
Nominal voltage (Min-Max)	207-253 V
Nominal current (Min-Max)	261-545 mA
Type of control gear	Not required
With control gear	No
Dimmable	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off (trailing edge)	No
Dimming phase cut-on (leading edge)	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Touch and Dim	No

Luminous flux in emergency mode	710 lm
Suitable for emergency lighting	No
With movement sensor	No
With light sensor	No
Covering of the luminaire with thermally insulating material possible	No
With air slots	No
Suitable for lamp power (Min-Max)	60-60 W
Luminaire efficacy (Min-Max)	0-0 lm/W
Max. system power	60 W
Rated luminous flux according to IEC 62722-2- 1 (Min-Max)	710-710 lm
Colour of light	White
Colour temperature (Min-Max)	2700-2700 K
Colour rendering index CRI	90-100
Width	126 mm
Height/depth	105 mm
Length	175 mm
Built-in length	175 mm
Luminous intensity (Min-Max)	0-0 cd
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Documentation

Regulated Substances Compliance

- LGRP-00121-V01.01-EN.pdf | PDF (0.57Mo)
- RoHS Certificate of Compliance | PDF
- Manufacturer REACH Declaration | PDF

CATALOGUE PAGE & OTHERS

- ex223001_0901.pdf | PDF (0.09Mo)
- ex223001_0902.pdf | PDF (0.09Mo)